



## Model: *Roll In Ruby* **RMR1T**

Project: .....

Location: .....

Item #: .....

Quantity: .....

Variant	Op Temp & Storage
HRMR1T	+1/+4°C
CFRMR1T	0/+3°C
MRMR1T	2/+2°C
LRMR1T	-18/-22°C

### Optional Features

- Glass door on high temp and chilled models
- Roll through designs
- Remote installation
- Floor Tray
- Lighting
- White food safe PVC exterior
- Including 2/1 Gastronorm Trolley

### Key Features

- Modular construction facilitates installation in areas with restricted access
- Hard wearing, stainless steel exterior to withstand the rigors of busy commercial kitchens
- Accommodates 1/1 and 2/1 Gastronorm or Euronorm Trolleys
- Hygienic stainless steel interior for fast, easy cleaning
- Digital temperature controller with built-in alarm and fail safe run facility
- Available in a range of temperatures to store general produce, chilled food, meat and frozen food
- 90mm environmentally friendly GWP low foam insulation for maximum efficiency and performance
- Top mounted pod refrigeration system for easy installation and servicing
- Automatic electric defrost and vaporiser system
- A choice of one, two and three door configurations fitted with self-closing doors with 90° dwell with easy to clean and replace magnetic balloon gasket
- Designed and built to ISO9001-2000 Quality management Standards
- HACCP compliant





## Dimensions

	HRMR1T	CFRMR1T	MRMR1T	LRMR1T
<b>External (mm):</b>	H2370 W905 D982	H2370 W905 D982	H2370 W905 D982	H2460 W905 D982
<b>Internal (mm):</b>	H1890 W689 D814	H1890 W689 D814	H1890 W689 D814	H1890 W689 D814
<b>Door Opening (mm):</b>	D1776	D1776	D1776	D1776
<b>Packed:</b>	H1600 W629 D2050	H1600 W1050 D2050	H1600 W629 D2050	H1700 W1050 D2050
<b>Weight:</b> <i>Add 5kg per product for packing</i>	195kg	195kg	195kg	200Kg

## Important Information

	HRMR1T	CFRMR1T	MRMR1T	LRMR1T
<b>Capacity:</b> cu.ft./litres				
<b>Construction:</b> Exterior (SS) Interior Door	0.7mm stainless steel 0.7mm stainless steel 0.7 stainless ext / 0.7 stainless int	0.7mm stainless steel 0.7mm stainless steel 0.7 stainless ext / 0.7 stainless int	0.7mm stainless steel 0.7mm stainless steel 0.7 stainless ext / 0.7 stainless int	0.7mm stainless steel 0.7mm stainless steel 0.7 stainless ext / 0.7 stainless int
<b>Power Supply:</b>	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
<b>Power Input:</b> Start Up Running Compressor HP	amps 7 amps 1/2	amps 7 amps 1/2	amps 7 amps 1/2	amps 7 amps 3/4
<b>Refrigerant::</b>	R134a	R134a	R134a	R404a
<b>Defrost:</b>	Automatic electric defrost and vaporisation	Automatic electric defrost and vaporisation	Automatic electric defrost and vaporisation	Automatic electric defrost and vaporisation
<b>Insulation:</b> GWP low foam insulation	90mm	90mm	90mm	90mm
<b>Fittings:</b> Shelves  Trayslides	1 x 2/1GN Gastronorm/Euronorm trolley (not included)  N/A	1 x 2/1GN Gastronorm/Euronorm trolley (not included)  N/A	1 x 2/1GN Gastronorm/Euronorm trolley (not included)  N/A	1 x 2/1GN Gastronorm/Euronorm trolley (not included)  N/A

**Allow minimum of 500mm above cabinet for maintenance and ventilation. All refrigeration equipment require adequate ventilation for efficient and effective performance.**

*Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.*



Williams Refrigeration  
Bryggen Road, North Lynn Industrial Estate King's Lynn, PE30 2HZ.  
Tel: +44 (0)1553 817 000 Fax: +44 (0)1553 817 111 Spares: +44 (0)1553 817017  
Website: [www.williams-refrigeration.com](http://www.williams-refrigeration.com) e.mail: [info@williams-refrigeration.co.uk](mailto:info@williams-refrigeration.co.uk)



V3 - CM/05/09

